

Overview Signal Towers

Whether they are used on machinery and equipment, manual workstations or for access control and point-of-sale systems, WERMA signal towers reliably signal different statuses, such as faults or material replenishment requests. Professional signalling provides your application with greater safety and security and considerably reduces response times. The urgency of the signal can be easily increased using different signal effects. This enables employees to immediately react to faults and quickly resolve any problems that arise.

Monitor your processes, make them reliable and keep them running - saving time and money. We call this intelligent signalling technology.

Overview Signal Towers

Product type		modular	modular	modular	modular	pre-assembled
Technical details		KombiSIGN 40	KombiSIGN 72	KombiSIGN 71	CO ₂ traffic light	KOMPAKT 37
Diameter*	Product range	40 mm	70 mm	70 mm	70 mm	37.5 mm
Dimensions*						
Voltage	12 V	•	•	•		•
	24 V			•		•
	115 V			•	•	
	230 V					
Protection rating	IP 66/69k	IP 65	IP 65	IP 20	IP 65	
Number of tiers possible	1-5	1-5	1-5	3	1-5	
Interface	I/O-Link	ASI, USB, I/O-Link, SmartMONITOR, WeASSIST	ASI, USB, I/O-Link, SmartMONITOR, WeASSIST			
Page		Page 26	Page 32	Page 38	Page 58	Page 60

* Technical diagrams can be found on the product page

Modular Signal Towers

Optical and audible signal elements can be combined flexibly in the modular signal towers. The modular design also enables customers to add other elements separately when required. The mechanical and electrical connection of the signal tower elements takes mere seconds thanks to the bayonet fitting.

Completely pre-assembled Signal Towers

Completely pre-assembled WERMA Signal Towers can be ordered as a compact unit under a single part number, which reduces ordering and installation effort. Impressive features include their stylish design and diverse installation options, allowing them to be used in a wide range of areas.

Product type		pre-assembled	pre-assembled	pre-assembled	pre-assembled	pre-assembled	pre-assembled
Technical details		eSIGN	RST 56	deSIGN 42	CleanSIGN	FlatsIGN	VarioSIGN
Diameter*		72,5 mm	57 mm	42 mm	70 mm	-	-
Dimensions*					112 mm x 125 mm	195 mm x 105 mm	62 mm x 90 mm
Voltage	12 V	•	•	•	•	•	•
	24 V					•	
	115 V					•	
	230 V					•	
Protection rating	IP 66/69k	IP 66/69k	IP 65	IP 67/IP 69k	IP 65	IP 65	
Number of tiers possible	6, 9, 15	2-5	2-3	3	3	3	
Interface	I/O-Link						
Page		Page 64	Page 68	Page 72	Page 74	Page 76	Page 78